

892323

County Washington
Quad Marine On
Quad ID 118A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date11/26/2025
Update Date03/19/2026
Received Date12/08/2025

Well Name GRADY, CHAD	Township 31	Range 20	Dir Section W 26	Subsection DBDABC	Well Depth 73 ft.	Depth Completed 73 ft.	Date Well Completed 11/24/2025																								
Elevation 869.4	Elev. Method LiDAR 1m DEM (MNDNR)					Drill Method Non-specified Rotary	Drill Fluid Water																								
Address C/W13294 PANORAMA AV N STILLWATER MN 55082					Use domestic	Status Active																									
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>FINE SAND</td><td>0</td><td>15</td><td>BROWN</td><td>MEDIUM</td></tr><tr><td>COARSE SAND</td><td>15</td><td>30</td><td>BLK/WHT</td><td>MEDIUM</td></tr><tr><td>MUDDY GRAVEL</td><td>30</td><td>58</td><td>BROWN</td><td>SOFT</td></tr><tr><td>WATER SAND</td><td>58</td><td>73</td><td>BROWN</td><td>MEDIUM</td></tr></table>					Geological Material	From	To (ft.)	Color	Hardness	FINE SAND	0	15	BROWN	MEDIUM	COARSE SAND	15	30	BLK/WHT	MEDIUM	MUDDY GRAVEL	30	58	BROWN	SOFT	WATER SAND	58	73	BROWN	MEDIUM	Well Hydrofractured? Yes ☐ No ☒	From To
					Geological Material	From	To (ft.)	Color	Hardness																						
					FINE SAND	0	15	BROWN	MEDIUM																						
					COARSE SAND	15	30	BLK/WHT	MEDIUM																						
					MUDDY GRAVEL	30	58	BROWN	SOFT																						
					WATER SAND	58	73	BROWN	MEDIUM																						
					Casing Type Single casing	Joint Threaded																									
					Drive Shoe? Yes ☒ No ☐	Above/Below																									
					Casing Diameter 4 in. To 69 ft.	Weight 10.89 lbs./ft.	Hole Diameter 4 in. To 73 ft.																								
					Open Hole Fromft. Toft.																										
Screen? Diameter4 in.	☒ Slot/Gauze 25	Type telescoping Length6.6 ft.	Make Set JOHNSON 69 ft. 73 ft.																												
Static Water Level 7.5 ft. land surface Measure 11/21/2025																															
Pumping Level (below land surface) 15.5 ft. 1 hrs. Pumping at 20 g.p.m.																															
Wellhead Completion Pitless adapter manufacturer WHITEWATER Model 5.5 BURY ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																															
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite 1.5 Sacks 6 ft. 10 ft. driven casing seal 1.5 Sacks 10 ft. 69 ft.																															
Nearest Known Source of Contamination 50 feet Southwes Direction Sewer Type Well disinfected upon completion? ☒ Yes ☐ No																															
Pump ☐ Not Installed Date Installed 11/21/2025 Manufacturer's name FRANKLIN ELECTRIC Model Number 10FA05S4 HP 0.5 Volt 230 Length of drop pipe 31 ft Capacity 11 g.p. Typ Submersible																															
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																															
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																															
Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft Located by Minnesota Geological Survey Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or System UTM - NAD83, Zone 15, Meters X 515646 Y 4998869 Unique Number Verification Info/GPS from data Input Date 11/26/2025																															
Angled Drill Hole																															
Well Contractor Salverda Well Co. 1497 SALVERDA, W. Licensee Business Lic. or Reg. No. Name of Driller																															