

892876

County Hennepin
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 02/17/2026
Received Date 10/24/2025

Well Name KOPPELMAN,	Township 117	Range 23	Dir W	Section 24	Subsection AAC																														
Elevation Elev. Method																																			
Address Contact 18340 MINNETONKA BL WAYZATA MN 55391 Well 3935 WALDEN SHORES RD DEEPHAVEN MN 55391																																			
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>CLAY</td><td>0</td><td>1</td><td>YELLOW</td><td>SOFT</td></tr><tr><td>GRAVEL</td><td>1</td><td>55</td><td>BROWN</td><td>SOFT</td></tr><tr><td>SANDY CLAY</td><td>55</td><td>80</td><td>BROWN</td><td>SOFT</td></tr><tr><td>CLAY</td><td>80</td><td>90</td><td>GRAY</td><td>SOFT</td></tr><tr><td>SAND</td><td>90</td><td>140</td><td>BROWN</td><td>SOFT</td></tr></table>						Geological Material	From	To (ft.)	Color	Hardness	CLAY	0	1	YELLOW	SOFT	GRAVEL	1	55	BROWN	SOFT	SANDY CLAY	55	80	BROWN	SOFT	CLAY	80	90	GRAY	SOFT	SAND	90	140	BROWN	SOFT
Geological Material	From	To (ft.)	Color	Hardness																															
CLAY	0	1	YELLOW	SOFT																															
GRAVEL	1	55	BROWN	SOFT																															
SANDY CLAY	55	80	BROWN	SOFT																															
CLAY	80	90	GRAY	SOFT																															
SAND	90	140	BROWN	SOFT																															
Well Depth 140 ft.																																			
Depth Completed 140 ft.																																			
Date Well Completed 08/29/2025																																			
Drill Method Non-specified Rotary																																			
Drill Fluid Qwik gel																																			
Use domestic																																			
Status Sealed																																			
Well Hydrofractured? Yes ☐ No ☒ From To																																			
Casing Type Single casing																																			
Joint																																			
Drive Shoe? Yes ☐ No ☐ Above/Below																																			
Casing Diameter Weight Hole Diameter																																			
4 in. To 135 ft. lbs./ft. 8 in. To 50 ft.																																			
7 in. To 140 ft.																																			
Open Hole From ft. To ft.																																			
Screen? ☒ Type stainless Make JOHNSON																																			
Diameter Slot/Gauze Length Set																																			
2 in. 18 5 ft. 135 ft. 140 ft.																																			
Static Water Level																																			
75 ft. land surface Measure 08/29/2025																																			
Pumping Level (below land surface)																																			
120 ft. 2 hrs. Pumping at 45 g.p.m.																																			
Wellhead Completion																																			
Pitless adapter manufacturer MERRIL Model SMCK414																																			
☐ Casing Protection ☒ 12 in. above grade																																			
☐ At-grade (Environmental Wells and Borings ONLY)																																			
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified																																			
Material Amount From To																																			
other 4 Sacks 70 ft. ft.																																			
cuttings 2 Cubic yards 70 ft. 140 ft.																																			
Nearest Known Source of Contamination																																			
28 feet North Direction Septic tank/drain field Type																																			
Well disinfected upon completion? ☒ Yes ☐ No																																			
Pump ☐ Not Installed Date Installed 08/29/2025																																			
Manufacturer's name GOULDS																																			
Model Number G45GS30 HP 3 Volt																																			
Length of drop pipe 120 ft Capacity 40 g.p. Typ Submersible																																			
Abandoned																																			
Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																																			
Variance																																			
Was a variance granted from the MDH for this well? ☐ Yes ☒ No																																			
Miscellaneous																																			
First Bedrock Aquifer																																			
Last Strat Depth to Bedrock ft																																			
Located by																																			
Locate Method																																			
System UTM - NAD83, Zone 15, Meters X Y																																			
Unique Number Verification Input Date																																			
Angled Drill Hole																																			
Well Contractor																																			
Braunwarth Well, LLP 1316 BRAUNWARTH, N																																			
Licensee Business Lic. or Reg. No. Name of Driller																																			