

892960

County Wadena
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 01/13/2026
Received Date 06/09/2025

Well Name DRESSEL, MARK 137					Township 33		Range W 9		Dir Section AAB		Well Depth 59 ft.		Depth Completed 59 ft.		Date Well Completed 05/21/2025																																
Elevation					Elev. Method					Drill Method Non-specified Rotary			Drill Fluid Bentonite																																		
Address C/W 33125 HUNTERSVILLE RD SEBEKA MN 56477												Use domestic		Status Active																																	
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>TOP SOIL</td><td>0</td><td>1</td><td>BLACK</td><td>SOFT</td></tr><tr><td>SAND</td><td>1</td><td>8</td><td>BROWN</td><td>SOFT</td></tr><tr><td>CLAY</td><td>8</td><td>27</td><td>BROWN</td><td>MEDIUM</td></tr><tr><td>SANDY CLAY</td><td>27</td><td>51</td><td>GRAY</td><td>MEDIUM</td></tr><tr><td>SAND</td><td>51</td><td>59</td><td>GRAY</td><td>SOFT</td></tr></table>												Geological Material	From	To (ft.)	Color	Hardness	TOP SOIL	0	1	BLACK	SOFT	SAND	1	8	BROWN	SOFT	CLAY	8	27	BROWN	MEDIUM	SANDY CLAY	27	51	GRAY	MEDIUM	SAND	51	59	GRAY	SOFT	Well Hydrofractured? Yes ☐ No ☒		From		To	
												Geological Material	From	To (ft.)	Color	Hardness																															
												TOP SOIL	0	1	BLACK	SOFT																															
												SAND	1	8	BROWN	SOFT																															
												CLAY	8	27	BROWN	MEDIUM																															
												SANDY CLAY	27	51	GRAY	MEDIUM																															
												SAND	51	59	GRAY	SOFT																															
												Casing Type Single casing		Joint																																	
												Drive Shoe? Yes ☐ No ☐		Above/Below																																	
												Casing Diameter 4 in. To 55 ft. 2 lbs./ft.		Hole Diameter 6.7 in. To 59 ft.																																	
Open Hole From ft. To ft.		Screen? ☒		Type stainless		Make JOHNSON																																									
Diameter 3 in.		Slot/Gauze 12		Length 4 ft.		Set 55 ft. 59 ft.																																									
Static Water Level 6 ft. land surface Measure 05/21/2025																																															
Pumping Level (below land surface) 55 ft. 1 hrs. Pumping at 30 g.p.m.																																															
Wellhead Completion Pitless adapter manufacturer Model ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																																															
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To other 3 Sacks ft. 45 ft.																																															
Nearest Known Source of Contamination 55 feet Southwes Direction Septic tank/drain field Type Well disinfected upon completion? ☒ Yes ☐ No																																															
Pump ☒ Not Installed Date Installed Manufacturer's name Model Number HP Volt Length of drop pipe ft Capacity g.p. Typ																																															
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																																															
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																																															
Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft Located by Locate Method System UTM - NAD83, Zone 15, Meters X Y Unique Number Verification Input Date																																															
Angled Drill Hole																																															
Well Contractor Doug's Water Wells 6217 WESA, DOUG Licensee Business Lic. or Reg. No. Name of Driller																																															