

893101

County Scott
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 04/07/2026
Received Date 12/05/2025

Well Name THOMPSON,					Township 113	Range 21	Dir Section W 14	Subsection BCA	Well Depth 235 ft.		Depth Completed 235 ft.		Date Well Completed 11/17/2025																																
Elevation					Elev. Method					Drill Method Non-specified Rotary		Drill Fluid Water																																	
Address C/W 10008 245TH ST E LAKEVILLE MN 55044									Use domestic		Status Active																																		
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>CLAY & SAND</td><td>0</td><td>14</td><td>BROWN</td><td>SOFT</td></tr><tr><td>CLAY & SAND</td><td>14</td><td>50</td><td>GRAY</td><td>SOFT</td></tr><tr><td>CLAY & SAND</td><td>50</td><td>205</td><td>GRAY</td><td>MEDIUM</td></tr><tr><td>WEATHERED ROCK</td><td>205</td><td>210</td><td>BROWN</td><td>MEDIUM</td></tr><tr><td>SANDROCK & SHALE</td><td>210</td><td>220</td><td>WHITE</td><td>SOFT</td></tr><tr><td>LIMEROCK</td><td>220</td><td>235</td><td>BROWN</td><td>MED-HRD</td></tr></table>									Geological Material	From	To (ft.)	Color	Hardness	CLAY & SAND	0	14	BROWN	SOFT	CLAY & SAND	14	50	GRAY	SOFT	CLAY & SAND	50	205	GRAY	MEDIUM	WEATHERED ROCK	205	210	BROWN	MEDIUM	SANDROCK & SHALE	210	220	WHITE	SOFT	LIMEROCK	220	235	BROWN	MED-HRD	Well Hydrofractured? Yes ☐ No ☒ From To	
									Geological Material	From	To (ft.)	Color	Hardness																																
									CLAY & SAND	0	14	BROWN	SOFT																																
									CLAY & SAND	14	50	GRAY	SOFT																																
									CLAY & SAND	50	205	GRAY	MEDIUM																																
									WEATHERED ROCK	205	210	BROWN	MEDIUM																																
									SANDROCK & SHALE	210	220	WHITE	SOFT																																
									LIMEROCK	220	235	BROWN	MED-HRD																																
									Casing Type Single casing		Joint Welded																																		
									Drive Shoe? Yes ☒ No ☐		Above/Below																																		
Casing Diameter 4 in. To		Weight 220 ft. 11 lbs./ft.		Hole Diameter 6.5 in. To 210 ft. 4 in. To 235 ft.																																									
Open Hole Screen? ☐		From 220 ft. To 235 ft.		Type Make																																									
Static Water Level 100 ft. land surface Measure 11/03/2025																																													
Pumping Level (below land surface) ft. hrs. Pumping at g.p.m.																																													
Wellhead Completion Pitless adapter manufacturer MONITOR Model ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																																													
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite 5 Sacks ft. 210 ft.																																													
Nearest Known Source of Contamination 54 feet West Direction Sewer Type Well disinfected upon completion? ☒ Yes ☐ No																																													
Pump ☐ Not Installed Date Installed 11/17/2025 Manufacturer's name F&W Model Number 4F19S15 HP 1.5 Volt 230 Length of drop pipe 126 ft Capacity 19 g.p. Typ Submersible																																													
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																																													
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																																													
Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft Located by Locate Method System UTM - NAD83, Zone 15, Meters X Y Unique Number Verification Input Date																																													
Angled Drill Hole																																													
Well Contractor Hartmann Well Co., LLP 1622 HARTMANN, W. Licensee Business Lic. or Reg. No. Name of Driller																																													