

893136

County Scott
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 04/10/2026
Received Date 12/05/2025

Well Name REIMER, BLAKE					Township 114	Range 21	Dir W	Section 31	Subsection AAA	Well Depth 235 ft.		Depth Completed 235 ft.		Date Well Completed 11/20/2025																																														
Elevation					Elev. Method					Drill Method Non-specified Rotary		Drill Fluid Water																																																
Address C/W 6945 210TH ST E PRIOR LAKE MN 55372										Use domestic		Status Active																																																
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>CLAY & SAND</td><td>0</td><td>14</td><td>BROWN</td><td>SOFT</td></tr><tr><td>CLAY & SAND</td><td>14</td><td>32</td><td>GRAY</td><td>SOFT</td></tr><tr><td>SAND, ROCK, CLAY</td><td>32</td><td>70</td><td>GRAY</td><td>SFT-MED</td></tr><tr><td>SAND</td><td>70</td><td>97</td><td>BROWN</td><td>SOFT</td></tr><tr><td>CLAY & SAND</td><td>97</td><td>165</td><td>GRAY</td><td>MEDIUM</td></tr><tr><td>BROKEN ROCK</td><td>165</td><td>168</td><td>BROWN</td><td>SOFT</td></tr><tr><td>LIMEROCK</td><td>168</td><td>174</td><td>BROWN</td><td>MED-HRD</td></tr><tr><td>LIMEROCK</td><td>174</td><td>235</td><td>BROWN</td><td>HARD</td></tr></table>										Geological Material	From	To (ft.)	Color	Hardness	CLAY & SAND	0	14	BROWN	SOFT	CLAY & SAND	14	32	GRAY	SOFT	SAND, ROCK, CLAY	32	70	GRAY	SFT-MED	SAND	70	97	BROWN	SOFT	CLAY & SAND	97	165	GRAY	MEDIUM	BROKEN ROCK	165	168	BROWN	SOFT	LIMEROCK	168	174	BROWN	MED-HRD	LIMEROCK	174	235	BROWN	HARD	Well Hydrofractured? Yes ☐ No ☒		From To			
										Geological Material	From	To (ft.)	Color	Hardness																																														
										CLAY & SAND	0	14	BROWN	SOFT																																														
										CLAY & SAND	14	32	GRAY	SOFT																																														
										SAND, ROCK, CLAY	32	70	GRAY	SFT-MED																																														
										SAND	70	97	BROWN	SOFT																																														
										CLAY & SAND	97	165	GRAY	MEDIUM																																														
										BROKEN ROCK	165	168	BROWN	SOFT																																														
										LIMEROCK	168	174	BROWN	MED-HRD																																														
										LIMEROCK	174	235	BROWN	HARD																																														
Casing Type Single casing		Joint Welded																																																										
Drive Shoe? Yes ☒ No ☐		Above/Below																																																										
Casing Diameter 4 in. To		Weight 109 ft. 11 lbs./ft.						Hole Diameter 6.5 in. To 169 ft. 4 in. To 235 ft.																																																				
Open Hole Screen? ☐		From 169 ft.		To 235 ft.																																																								
		Type		Make																																																								
Static Water Level 58 ft. land surface Measure 11/04/2025																																																												
Pumping Level (below land surface) ft. hrs. Pumping at g.p.m.																																																												
Wellhead Completion Pitless adapter manufacturer MONITOR Model ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																																																												
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite 4 Sacks ft. 169 ft.																																																												
Nearest Known Source of Contamination 62 feet Southwes Direction Sewer Type Well disinfected upon completion? ☒ Yes ☐ No																																																												
Pump ☐ Not Installed Date Installed 11/20/2025 Manufacturer's name F&W Model Number 4F19S15 HP 1.5 Volt 230 Length of drop pipe 105 ft Capacity 19 g.p. Typ Submersible																																																												
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																																																												
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																																																												
Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft Located by Locate Method System UTM - NAD83, Zone 15, Meters X Y Unique Number Verification Input Date																																																												
Angled Drill Hole																																																												
Well Contractor Hartmann Well Co., LLP 1622 HARTMANN, W. Licensee Business Lic. or Reg. No. Name of Driller																																																												