

893995

CountyOtter Tail

Quad

Quad ID

MINNESOTA DEPARTMENT OF HEALTH

WELL AND BORING REPORT

Minnesota Statutes Chapter 1031

Entry Date03/16/2026

Update Date03/16/2026

Received Date12/02/2025

Well NameTownshipRangeDir SectionSubsection JR MATT13741W 21BDD ElevationElev. Method					Well DepthDepth CompletedDate Well Completed 109 ft.109 ft.11/04/2025 Drill MethodNon-specified RotaryDrill FluidQwik gel																																		
Address Well465 OAK CIRCLE VERGAS MN 56587 ContactVERGAS MN 56587					Use domesticStatusActive Well Hydrofractured?YesNoFromTo Casing TypeSingle casingJoint Drive Shoe?YesNoAbove/Below																																		
Stratigraphy Information <table><thead><tr><th>Geological Material</th><th>From</th><th>To (ft.)</th><th>Color</th><th>Hardness</th></tr></thead><tbody><tr><td>GRAVEL/ COBBLE</td><td>0</td><td>30</td><td>BROWN</td><td>MEDIUM</td></tr><tr><td>CLAY/ ROCK</td><td>30</td><td>44</td><td>GRAY</td><td>HARD</td></tr><tr><td>SAND</td><td>44</td><td>67</td><td>GRAY</td><td>MEDIUM</td></tr><tr><td>SANDY CLAY</td><td>67</td><td>80</td><td>GRAY</td><td>SOFT</td></tr><tr><td>SAND</td><td>80</td><td>109</td><td>GRAY</td><td>SOFT</td></tr></tbody></table>					Geological Material	From	To (ft.)	Color	Hardness	GRAVEL/ COBBLE	0	30	BROWN	MEDIUM	CLAY/ ROCK	30	44	GRAY	HARD	SAND	44	67	GRAY	MEDIUM	SANDY CLAY	67	80	GRAY	SOFT	SAND	80	109	GRAY	SOFT	Casing DiameterWeightHole Diameter 4 in. To 104 ft. lbs./ft.6.7 in. To 109 ft.				
Geological Material	From	To (ft.)	Color	Hardness																																			
GRAVEL/ COBBLE	0	30	BROWN	MEDIUM																																			
CLAY/ ROCK	30	44	GRAY	HARD																																			
SAND	44	67	GRAY	MEDIUM																																			
SANDY CLAY	67	80	GRAY	SOFT																																			
SAND	80	109	GRAY	SOFT																																			
					Open HoleFromft.Toft. Screen?Type telescopingMakeJOHNSON DiameterSlot/GauzeLengthSet 3.7 in. 10 5 ft. 104 ft. 109 ft.																																		
					Static Water Level 49 ft. land surfaceMeasure11/04/2025																																		
					Pumping Level (below land surface) 104 ft. 1 hrs. Pumping at60 g.p.m.																																		
					Wellhead Completion Pitless adapter manufacturerModel Casing Protection12 in. above grade At-grade (Environmental Wells and Borings ONLY)																																		
					Grouting InformationWell Grouted?YesNoNot Specified MaterialAmountFromTo bentonite6 Sacksft. 60 ft.																																		
					Nearest Known Source of Contamination feetDirectionType Well disinfected upon completion?YesNo																																		
					PumpNot InstalledDate Installed Manufacturer's name Model NumberHPVolt Length of drop pipeft Capacityg.p. Typ																																		
					Abandoned Does property have any not in use and not sealed well(s)?YesNo																																		
					Variance Was a variance granted from the MDH for this well?YesNo																																		
					Miscellaneous First BedrockAquifer Last StratDepth to Bedrockft Located by Locate Method SystemUTM - NAD83, Zone 15, MetersXY Unique Number VerificationInput Date																																		
					Angled Drill Hole																																		
					Well Contractor Johnson and Sons Well1345EWERT, C Licensee BusinessLic. or Reg. No.Name of Driller																																		
Minnesota Well Index Report					893995		Printed on 08/13/2026 HE-01205-15																																