

894364

County Aitkin
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 02/02/2026
Update Date 02/02/2026
Received Date 10/09/2025

Well Name CABIN LIFERS	Township 40	Range 26	Dir W	Section 16	Subsection ADB																									
Elevation Elev. Method																														
Address Well 49374 372ND PL MN Contact 38315 496TH LA PALISADE MN 56431																														
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>CLAY + ROCKS</td><td>0</td><td>8</td><td>BROWN</td><td>MEDIUM</td></tr><tr><td>SAND</td><td>8</td><td>24</td><td>GRAY</td><td>MEDIUM</td></tr><tr><td>CLAY</td><td>24</td><td>46</td><td>GRAY</td><td>MEDIUM</td></tr><tr><td>SAND</td><td>46</td><td>64</td><td>BROWN</td><td>MEDIUM</td></tr></table>						Geological Material	From	To (ft.)	Color	Hardness	CLAY + ROCKS	0	8	BROWN	MEDIUM	SAND	8	24	GRAY	MEDIUM	CLAY	24	46	GRAY	MEDIUM	SAND	46	64	BROWN	MEDIUM
Geological Material	From	To (ft.)	Color	Hardness																										
CLAY + ROCKS	0	8	BROWN	MEDIUM																										
SAND	8	24	GRAY	MEDIUM																										
CLAY	24	46	GRAY	MEDIUM																										
SAND	46	64	BROWN	MEDIUM																										
Well Depth 64 ft. Depth Completed 64 ft. Date Well Completed 07/15/2025																														
Drill Method Non-specified Rotary Drill Fluid Bentonite																														
Use domestic Status Active																														
Well Hydrofractured? Yes ☐ No ☒ From To																														
Casing Type Single casing Joint																														
Drive Shoe? Yes ☐ No ☐ Above/Below																														
Casing Diameter 4 in. Weight 56 lbs./ft. Hole Diameter 6.5 in. To 64 ft.																														
Open Hole From ft. To ft.																														
Screen? ☒ Type stainless Make JOHNSON Diameter Slot/Gauze Length Set 2 in. 8 ft. ft. ft.																														
Static Water Level 8 ft. land surface Measure 07/15/2025																														
Pumping Level (below land surface) 60 ft. 1 hrs. Pumping at 5 g.p.m.																														
Wellhead Completion Pitless adapter manufacturer Model ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																														
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite ft. ft.																														
Nearest Known Source of Contamination 50 feet Direction Type Well disinfected upon completion? ☐ Yes ☐ No																														
Pump ☐ Not Installed Date Installed Manufacturer's name STA-RITE Model Number HP 0.5 Volt 115 Length of drop pipe ft Capacity 5 g.p. Typ																														
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																														
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																														
Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft Located by Locate Method System UTM - NAD83, Zone 15, Meters X Y Unique Number Verification Input Date																														
Angled Drill Hole																														
Well Contractor Hasskamp Bros. Well Drilling 1585 CHAD + CORY Licensee Business Lic. or Reg. No. Name of Driller																														