

894406

County Dodge
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 02/09/2026
Received Date 12/04/2025

Well Name LORETTA HIMLE 105					Township 105	Range 16	Dir W	Section 3	Subsection BAC
Elevation					Elev. Method				
Address C/W 25291 700TH ST KASSON MN 55944									
Stratigraphy Information									
Geological Material		From	To (ft.)	Color	Hardness				
CLAY		0	13	BROWN	SOFT				
SAND		13	18	TAN	SOFT				
CLAY		18	43	GRAY	SOFT				
CLAY&SAND		43	83	GRAY	SOFT				
LIMESTONE		83	90	YELLOW	MEDIUM				
LIMESTONE		90	180	GRAY	HARD				
Well Depth 180 ft.					Depth Completed 180 ft.			Date Well Completed 11/19/2025	
Drill Method Non-specified Rotary					Drill Fluid Bentonite				
Use domestic					Status Sealed				
Well Hydrofractured? Yes ☐ No ☒					From To				
Casing Type Single casing					Joint Welded				
Drive Shoe? Yes ☒ No ☐					Above/Below				
Casing Diameter 4 in. To 83 ft. 10.79 lbs./ft.					Hole Diameter 12 in. To 65 ft.				
8 in. To 65 ft. lbs./ft.					8 in. To 83 ft.				
					4 in. To 180 ft.				
Open Hole From 83 ft. To 180 ft.									
Screen? ☐					Type Make				
Static Water Level 57 ft. land surface Measure 11/19/2025									
Pumping Level (below land surface) 80 ft. 2 hrs. Pumping at 25 g.p.m.									
Wellhead Completion Pitless adapter manufacturer BAKER Model ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)									
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To neat cement 1.25 Cubic yards 83 ft. ft.									
Nearest Known Source of Contamination 100 feet Direction Type Well disinfected upon completion? ☒ Yes ☐ No									
Pump ☐ Not Installed Date Installed 11/19/2025 Manufacturer's name GRUNDFOS Model Number 10SQ07-200 HP 0.75 Volt 230 Length of drop pipe ft Capacity 10 g.p. Typ Submersible									
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No									
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No									
Miscellaneous First Bedrock Last Strat Aquifer Depth to Bedrock ft Located by Locate Method System UTM - NAD83, Zone 15, Meters X Y Unique Number Verification Input Date									
Angled Drill Hole									
Well Contractor Peterson Well Drilling, Inc. 2293 UNDERDAHL, N Licensee Business Lic. or Reg. No. Name of Driller									