

894799

County Todd
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 04/23/2026
Update Date 04/23/2026
Received Date 10/20/2025

Well Name WILTERMUTH,	Township 131	Range 34	Dir Section W 28	Subsection DDB	Well Depth 114 ft.	Depth Completed 110 ft.	Date Well Completed 10/06/2025																									
Elevation Elev. Method					Drill Method Non-specified Rotary	Drill Fluid Bentonite																										
Address C/W 34321 11 CO CLARISSA MN 56440					Use domestic	Status Active																										
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>CLAY</td><td>0</td><td>26</td><td>BROWN</td><td>MEDIUM</td></tr><tr><td>CLAY</td><td>26</td><td>101</td><td>GRAY</td><td>MEDIUM</td></tr><tr><td>SAND</td><td>101</td><td>111</td><td>GRAY</td><td>SOFT</td></tr><tr><td>CLAY</td><td>111</td><td>114</td><td>GRAY</td><td>MEDIUM</td></tr></table>					Geological Material	From	To (ft.)	Color	Hardness	CLAY	0	26	BROWN	MEDIUM	CLAY	26	101	GRAY	MEDIUM	SAND	101	111	GRAY	SOFT	CLAY	111	114	GRAY	MEDIUM	Well Hydrofractured? Yes ☐ No ☒ From To		
					Geological Material	From	To (ft.)	Color	Hardness																							
					CLAY	0	26	BROWN	MEDIUM																							
					CLAY	26	101	GRAY	MEDIUM																							
					SAND	101	111	GRAY	SOFT																							
					CLAY	111	114	GRAY	MEDIUM																							
					Casing Type Single casing Joint																											
					Drive Shoe? Yes ☐ No ☒ Above/Below																											
					Casing Diameter Weight Hole Diameter																											
					4 in. To 106 ft. lbs./ft. 6.7 in. To 114 ft.																											
Open Hole From ft. To ft.																																
Screen? ☒ Type stainless Make JOHNSON																																
Diameter Slot/Gauze Length Set																																
4 in. 25 4 ft. 106 ft. 110 ft.																																
Static Water Level 40 ft. land surface Measure 10/06/2025																																
Pumping Level (below land surface) ft. hrs. Pumping at g.p.m.																																
Wellhead Completion Pitless adapter manufacturer Model ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																																
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite Sacks ft. 4 ft.																																
Nearest Known Source of Contamination 50 feet East Direction Septic tank/drain field Type Well disinfected upon completion? ☒ Yes ☐ No																																
Pump ☒ Not Installed Date Installed Manufacturer's name Model Number HP Volt Length of drop pipe ft Capacity g.p. Typ																																
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																																
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																																
Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft Located by Locate Method System UTM - NAD83, Zone 15, Meters X Y Unique Number Verification Input Date																																
Angled Drill Hole																																
Well Contractor A and J Well Drilling, Inc. 1596 JAPP, A Licensee Business Lic. or Reg. No. Name of Driller																																