

894850

County Hubbard
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 02/17/2026
Update Date 02/17/2026
Received Date 12/22/2025

Well Name FOHRENBRUCH, 145	Township 145	Range 32	Dir Section W 26	Subsection DBA	Well Depth 133 ft.	Depth Completed 133 ft.	Date Well Completed 11/12/2025																									
Elevation Elev. Method					Drill Method Non-specified Rotary	Drill Fluid Bentonite																										
Address C/W 603 KAY AV SE BEMIDJI MN 56601					Use domestic	Status Active																										
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>SANDY CLAY</td><td>0</td><td>14</td><td>BROWN</td><td>MEDIUM</td></tr><tr><td>CLAY</td><td>14</td><td>107</td><td>GRAY</td><td>MEDIUM</td></tr><tr><td>FINE SAND</td><td>107</td><td>127</td><td>GRAY</td><td>SOFT</td></tr><tr><td>SAND</td><td>127</td><td>133</td><td>GRAY</td><td>SOFT</td></tr></table>					Geological Material	From	To (ft.)	Color	Hardness	SANDY CLAY	0	14	BROWN	MEDIUM	CLAY	14	107	GRAY	MEDIUM	FINE SAND	107	127	GRAY	SOFT	SAND	127	133	GRAY	SOFT	Well Hydrofractured? Yes ☐ No ☒ From To		
					Geological Material	From	To (ft.)	Color	Hardness																							
					SANDY CLAY	0	14	BROWN	MEDIUM																							
					CLAY	14	107	GRAY	MEDIUM																							
					FINE SAND	107	127	GRAY	SOFT																							
					SAND	127	133	GRAY	SOFT																							
					Casing Type Single casing Joint																											
					Drive Shoe? Yes ☐ No ☒ Above/Below																											
					Casing Diameter Weight Hole Diameter																											
					4 in. To 129 ft. 21 lbs./ft. 8 in. To 133 ft.																											
Open Hole From ft. To ft.																																
Screen? ☒ Type stainless Make JOHNSON																																
Diameter Slot/Gauze Length Set																																
2 in. 10 4 ft. 129 ft. 133 ft.																																
Static Water Level 14 ft. land surface Measure 11/12/2025																																
Pumping Level (below land surface) 70 ft. 2 hrs. Pumping at 35 g.p.m.																																
Wellhead Completion Pitless adapter manufacturer Model ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																																
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite 4 Sacks ft. 50 ft.																																
Nearest Known Source of Contamination 70 feet <u>Northeas</u> Direction <u>Septic tank/drain field</u> Type Well disinfected upon completion? ☒ Yes ☐ No																																
Pump ☒ Not Installed Date Installed Manufacturer's name Model Number HP Volt Length of drop pipe ft Capacity g.p. Typ																																
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																																
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																																
Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft Located by Locate Method System UTM - NAD83, Zone 15, Meters X Y Unique Number Verification Input Date																																
Angled Drill Hole																																
Well Contractor Antlers Well Drilling 1448 PINK, T Licensee Business Lic. or Reg. No. Name of Driller																																