

895102

County Beltrami
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date

Update Date01/12/2026

Received Date12/16/2025

Well NameNIPP, TORY & Elevation Address C/W19470 LOOKOUT TOWER RD NE HINES MN 56647					Well Depth135 ft. Drill MethodNon-specified Rotary Use domestic Well Hydrofractured?YesNoFromTo Casing TypeSingle casingJoint Drive Shoe?YesNoAbove/Below					Depth Completed135 ft. Drill FluidBentonite StatusActive					Date Well Completed11/04/2025																																																					
Stratigraphy Information <table><thead><tr><th>Geological Material</th><th>From</th><th>To (ft.)</th><th>Color</th><th>Hardness</th></tr></thead><tbody><tr><td>CLAY</td><td>0</td><td>10</td><td>BROWN</td><td>MED-HRD</td></tr><tr><td>CLAY</td><td>10</td><td>72</td><td>BLUE</td><td>MED-HRD</td></tr><tr><td>CLAY/ ROCKS</td><td>72</td><td>80</td><td>BLUE</td><td>MED-HRD</td></tr><tr><td>SAND/ CLAY</td><td>80</td><td>92</td><td>BLUE</td><td>SOFT</td></tr><tr><td>CLAY/ ROCKS</td><td>92</td><td>126</td><td>BLUE</td><td>MEDIUM</td></tr><tr><td>SAND</td><td>126</td><td>135</td><td>GREEN</td><td>MEDIUM</td></tr></tbody></table>										Geological Material	From	To (ft.)	Color	Hardness	CLAY	0	10	BROWN	MED-HRD	CLAY	10	72	BLUE	MED-HRD	CLAY/ ROCKS	72	80	BLUE	MED-HRD	SAND/ CLAY	80	92	BLUE	SOFT	CLAY/ ROCKS	92	126	BLUE	MEDIUM	SAND	126	135	GREEN	MEDIUM	Casing DiameterWeightHole Diameter <table><tbody><tr><td>4 in.</td><td>To</td><td>130 ft.</td><td>lbs./ft.</td><td>8 in.</td><td>To</td><td>50 ft.</td></tr><tr><td></td><td></td><td></td><td></td><td>6.5 in.</td><td>To</td><td>135 ft.</td></tr></tbody></table>										4 in.	To	130 ft.	lbs./ft.	8 in.	To	50 ft.					6.5 in.	To	135 ft.
Geological Material	From	To (ft.)	Color	Hardness																																																																
CLAY	0	10	BROWN	MED-HRD																																																																
CLAY	10	72	BLUE	MED-HRD																																																																
CLAY/ ROCKS	72	80	BLUE	MED-HRD																																																																
SAND/ CLAY	80	92	BLUE	SOFT																																																																
CLAY/ ROCKS	92	126	BLUE	MEDIUM																																																																
SAND	126	135	GREEN	MEDIUM																																																																
4 in.	To	130 ft.	lbs./ft.	8 in.	To	50 ft.																																																														
				6.5 in.	To	135 ft.																																																														
Open HoleFromft.Toft. Screen?☒TypeplasticMakeJOHNSON <table><tbody><tr><td>Diameter</td><td>Slot/Gauze</td><td>Length</td><td>Set</td></tr><tr><td>4 in.</td><td>15</td><td>5 ft.</td><td>130 ft.</td></tr><tr><td></td><td></td><td></td><td>135 ft.</td></tr></tbody></table>															Diameter	Slot/Gauze	Length	Set	4 in.	15	5 ft.	130 ft.				135 ft.																																										
Diameter	Slot/Gauze	Length	Set																																																																	
4 in.	15	5 ft.	130 ft.																																																																	
			135 ft.																																																																	
Static Water Level <table><tbody><tr><td>60 ft.</td><td>land surface</td><td>Measure</td><td>11/04/2025</td></tr></tbody></table>															60 ft.	land surface	Measure	11/04/2025																																																		
60 ft.	land surface	Measure	11/04/2025																																																																	
Pumping Level (below land surface) <table><tbody><tr><td>ft.</td><td>hrs.</td><td>Pumping at</td><td>g.p.m.</td></tr></tbody></table>															ft.	hrs.	Pumping at	g.p.m.																																																		
ft.	hrs.	Pumping at	g.p.m.																																																																	
Wellhead Completion <table><tbody><tr><td>Pitless adapter manufacturer</td><td>AQUA SEAL</td><td>Model</td><td>T41</td></tr><tr><td>☐ Casing Protection</td><td>☒ 12 in. above grade</td><td></td><td></td></tr><tr><td colspan="4">☐ At-grade (Environmental Wells and Borings ONLY)</td></tr></tbody></table>															Pitless adapter manufacturer	AQUA SEAL	Model	T41	☐ Casing Protection	☒ 12 in. above grade			☐ At-grade (Environmental Wells and Borings ONLY)																																													
Pitless adapter manufacturer	AQUA SEAL	Model	T41																																																																	
☐ Casing Protection	☒ 12 in. above grade																																																																			
☐ At-grade (Environmental Wells and Borings ONLY)																																																																				
Grouting Information <table><tbody><tr><td>Well Grouted?</td><td>☒ Yes</td><td>☐ No</td><td>☐ Not Specified</td></tr><tr><td>Material</td><td>Amount</td><td>From</td><td>To</td></tr><tr><td>bentonite</td><td>5 Sacks</td><td>ft.</td><td>50 ft.</td></tr></tbody></table>															Well Grouted?	☒ Yes	☐ No	☐ Not Specified	Material	Amount	From	To	bentonite	5 Sacks	ft.	50 ft.																																										
Well Grouted?	☒ Yes	☐ No	☐ Not Specified																																																																	
Material	Amount	From	To																																																																	
bentonite	5 Sacks	ft.	50 ft.																																																																	
Nearest Known Source of Contamination <table><tbody><tr><td>65 feet</td><td>South Direction</td><td>Septic tank/drain field</td><td>Type</td></tr><tr><td colspan="2">Well disinfected upon completion?</td><td>☒ Yes</td><td>☐ No</td></tr></tbody></table>															65 feet	South Direction	Septic tank/drain field	Type	Well disinfected upon completion?		☒ Yes	☐ No																																														
65 feet	South Direction	Septic tank/drain field	Type																																																																	
Well disinfected upon completion?		☒ Yes	☐ No																																																																	
Pump <table><tbody><tr><td>☐ Not Installed</td><td>Date Installed</td><td>11/12/2025</td></tr><tr><td colspan="3">Manufacturer's nameGRUNDFOS</td></tr><tr><td>Model Number</td><td>10SQ07</td><td>HP0.75</td><td>Volt220</td></tr><tr><td>Length of drop pipe</td><td>110 ft</td><td>Capacity10 g.p.</td><td>TypSubmersible</td></tr></tbody></table>															☐ Not Installed	Date Installed	11/12/2025	Manufacturer's nameGRUNDFOS			Model Number	10SQ07	HP0.75	Volt220	Length of drop pipe	110 ft	Capacity10 g.p.	TypSubmersible																																								
☐ Not Installed	Date Installed	11/12/2025																																																																		
Manufacturer's nameGRUNDFOS																																																																				
Model Number	10SQ07	HP0.75	Volt220																																																																	
Length of drop pipe	110 ft	Capacity10 g.p.	TypSubmersible																																																																	
Abandoned <table><tbody><tr><td>Does property have any not in use and not sealed well(s)?</td><td>☐ Yes</td><td>☒ No</td></tr></tbody></table>															Does property have any not in use and not sealed well(s)?	☐ Yes	☒ No																																																			
Does property have any not in use and not sealed well(s)?	☐ Yes	☒ No																																																																		
Variance <table><tbody><tr><td>Was a variance granted from the MDH for this well?</td><td>☐ Yes</td><td>☒ No</td></tr></tbody></table>															Was a variance granted from the MDH for this well?	☐ Yes	☒ No																																																			
Was a variance granted from the MDH for this well?	☐ Yes	☒ No																																																																		
Miscellaneous <table><tbody><tr><td>First Bedrock</td><td>Aquifer</td></tr><tr><td>Last Strat</td><td>Depth to Bedrock</td><td>ft</td></tr><tr><td colspan="2">Located by</td></tr><tr><td>Locate Method</td><td></td></tr><tr><td>System</td><td>UTM - NAD83, Zone 15, Meters</td><td>X</td><td>Y</td></tr><tr><td>Unique Number Verification</td><td></td><td></td><td>Input Date</td></tr></tbody></table>															First Bedrock	Aquifer	Last Strat	Depth to Bedrock	ft	Located by		Locate Method		System	UTM - NAD83, Zone 15, Meters	X	Y	Unique Number Verification			Input Date																																					
First Bedrock	Aquifer																																																																			
Last Strat	Depth to Bedrock	ft																																																																		
Located by																																																																				
Locate Method																																																																				
System	UTM - NAD83, Zone 15, Meters	X	Y																																																																	
Unique Number Verification			Input Date																																																																	
Angled Drill Hole																																																																				
Well Contractor <table><tbody><tr><td>Reed and Reed Water Well</td><td>1854</td><td>REED, J.</td></tr><tr><td>Licensee Business</td><td>Lic. or Reg. No.</td><td>Name of Driller</td></tr></tbody></table>															Reed and Reed Water Well	1854	REED, J.	Licensee Business	Lic. or Reg. No.	Name of Driller																																																
Reed and Reed Water Well	1854	REED, J.																																																																		
Licensee Business	Lic. or Reg. No.	Name of Driller																																																																		