

895372

County Mower

Quad

Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date04/27/2026

Update Date04/27/2026

Received Date12/19/2025

Well Name HAARSTAD,	Township 103	Range 16	Dir W	Section 2	Subsection DDD	Well Depth 178 ft.	Depth Completed 178 ft.	Date Well Completed 11/26/2025																								
Elevation	Elev. Method					Drill Method Non-specified Rotary	Drill Fluid	Other																								
Address						Use domestic	Status Active																									
C/W27017 670TH AV DEXTER MN 55926						Well Hydrofractured? Yes ☐ No ☒	From	To																								
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>CLAY</td><td>0</td><td>20</td><td>TAN</td><td>SOFT</td></tr><tr><td>CLAY</td><td>20</td><td>90</td><td>BLUE</td><td>SOFT</td></tr><tr><td>CLAY/ LIMESTONE</td><td>90</td><td>130</td><td>WHITE</td><td>SOFT</td></tr><tr><td>LIMESTONE</td><td>130</td><td>178</td><td>TAN</td><td>MEDIUM</td></tr></table>						Geological Material	From	To (ft.)	Color	Hardness	CLAY	0	20	TAN	SOFT	CLAY	20	90	BLUE	SOFT	CLAY/ LIMESTONE	90	130	WHITE	SOFT	LIMESTONE	130	178	TAN	MEDIUM	Casing Type Single casing	Joint Welded
						Geological Material	From	To (ft.)	Color	Hardness																						
						CLAY	0	20	TAN	SOFT																						
						CLAY	20	90	BLUE	SOFT																						
						CLAY/ LIMESTONE	90	130	WHITE	SOFT																						
						LIMESTONE	130	178	TAN	MEDIUM																						
						Drive Shoe? Yes ☒ No ☐	Above/Below																									
						Casing Diameter 4 in. To	Weight 132 ft.	lbs./ft.	Hole Diameter 8 in. To	132 ft.																						
									4 in. To	178 ft.																						
						Open Hole From 132 ft. To 178 ft.	Screen? ☐			Type	Make																					
Static Water Level 91 ft. land surface Measure 11/12/2025																																
Pumping Level (below land surface) 101 ft. 2 hrs. Pumping at 15 g.p.m.																																
Wellhead Completion Pitless adapter manufacturer BAKER Model 4X5 ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																																
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To neat cement 2 Cubic yards ft. 132 ft.																																
Nearest Known Source of Contamination 50 feet Direction Type Well disinfected upon completion? ☒ Yes ☐ No																																
Pump ☐ Not Installed Date Installed 11/26/2025 Manufacturer's name FLINT + WALLING Model Number 4F10S10301 HP 1 Volt 230 Length of drop pipe 115 ft Capacity 10 g.p. Typ Submersible																																
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																																
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																																
Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft Located by Locate Method System UTM - NAD83, Zone 15, Meters X Y Unique Number Verification Input Date																																
Angled Drill Hole																																
Well Contractor Thein Well Rochester, Inc. 2641 HANSON, B Licensee Business Lic. or Reg. No. Name of Driller																																