

895864

County Sherburne
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 05/05/2026
Update Date 05/05/2026
Received Date 01/12/2026

Well Name ANDERSON,	Township 35	Range 28	Dir Section W 1	Subsection CBD	Well Depth 106 ft.	Depth Completed 106 ft.	Date Well Completed 01/09/2026
Elevation	Elev. Method				Drill Method Non-specified Rotary	Drill Fluid	Other
Address C/W 18788 17TH ST PRINCETON MN 55371					Use domestic	Status Active	
Stratigraphy Information Geological Material From To (ft.) Color Hardness CLAY/ GRAVEL/ ROCK 0 98 DK. RED M.HARD SEAMS SAND/ CLAY 98 106 DARK HARD					Well Hydrofractured? Yes ☐ No ☐ From To		
					Casing Type Single casing Joint		
					Drive Shoe? Yes ☐ No ☐ Above/Below		
					Casing Diameter Weight		
					4 in. To 98 ft. lbs./ft.		
					Open Hole From ft. To ft.		
					Screen? ☒ Type stainless Make JOHNSON		
					Diameter Slot/Gauze Length Set		
					2 in. 12 8 ft. 98 ft. 106 ft.		
					Static Water Level		
10 ft. land surface Measure 01/09/2026							
Pumping Level (below land surface)							
104 ft. 1 hrs. Pumping at 2 g.p.m.							
Wellhead Completion							
Pitless adapter manufacturer MONITOR Model SNAPPY							
☐ Casing Protection ☒ 12 in. above grade							
☐ At-grade (Environmental Wells and Borings ONLY)							
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified							
Material Amount From To							
bentonite 6 Sacks ft. 50 ft.							
Nearest Known Source of Contamination							
50 feet North Direction Septic tank/drain field Type							
Well disinfected upon completion? ☒ Yes ☐ No							
Pump ☐ Not Installed Date Installed 01/09/2026							
Manufacturer's name STA-RITE							
Model Number HP 0.5 Volt 230							
Length of drop pipe 40 ft Capacity 2 g.p. Typ Submersible							
Abandoned							
Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No							
Variance							
Was a variance granted from the MDH for this well? ☐ Yes ☒ No							
Miscellaneous							
First Bedrock Aquifer							
Last Strat Depth to Bedrock ft							
Located by							
Locate Method							
System UTM - NAD83, Zone 15, Meters X Y							
Unique Number Verification Input Date							
Angled Drill Hole							
Well Contractor							
Fobbe Well, LLP 1919 FOBBE, R							
Licensee Business Lic. or Reg. No. Name of Driller							