

896205

County Todd
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 04/23/2026
Update Date 04/23/2026
Received Date 12/26/2025

Well Name LENK, MICHAEL	Township 132	Range 32	Dir W	Section 29	Subsection BAC																				
Elevation Elev. Method																									
Address Contact 28102 430TH ST BROWERVILLE MN 56438 Well 40711 PORTAGE CI BROWERVILLE MN 56438																									
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>SANDY CLAY</td><td>0</td><td>35</td><td>BROWN</td><td>MEDIUM</td></tr><tr><td>CLAY</td><td>35</td><td>51</td><td>BROWN</td><td>HARD</td></tr><tr><td>SAND (FINE)</td><td>51</td><td>59</td><td>BROWN</td><td>SOFT</td></tr></table>						Geological Material	From	To (ft.)	Color	Hardness	SANDY CLAY	0	35	BROWN	MEDIUM	CLAY	35	51	BROWN	HARD	SAND (FINE)	51	59	BROWN	SOFT
Geological Material	From	To (ft.)	Color	Hardness																					
SANDY CLAY	0	35	BROWN	MEDIUM																					
CLAY	35	51	BROWN	HARD																					
SAND (FINE)	51	59	BROWN	SOFT																					
Well Depth 59 ft. Depth Completed 59 ft. Date Well Completed 10/18/2025																									
Drill Method Non-specified Rotary Drill Fluid Bentonite																									
Use domestic Status Active																									
Well Hydrofractured? Yes ☐ No ☒ From To																									
Casing Type Single casing Joint																									
Drive Shoe? Yes ☐ No ☐ Above/Below																									
Casing Diameter 4 in. Weight 51 lbs./ft. Hole Diameter 7.8 in. To 59 ft.																									
Open Hole From ft. To ft.																									
Screen? ☒ Type telescoping Make JOHNSON																									
Diameter 3 in. Slot/Gauze 15 Length 8 ft. Set 51 ft. To 59 ft.																									
Static Water Level 18 ft. land surface Measure 10/18/2025																									
Pumping Level (below land surface) ft. hrs. Pumping at g.p.m.																									
Wellhead Completion Pitless adapter manufacturer BAKER Model BULLDOG ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																									
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified																									
Material bentonite Amount 5 Sacks From To ft. 45 ft.																									
Nearest Known Source of Contamination feet Direction Type																									
Well disinfected upon completion? ☒ Yes ☐ No																									
Pump ☐ Not Installed Date Installed 11/05/2025																									
Manufacturer's name FRANKLIN																									
Model Number HP 0.5 Volt 230																									
Length of drop pipe 39 ft Capacity 10 g.p. Typ Submersible																									
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																									
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																									
Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft Located by Locate Method System UTM - NAD83, Zone 15, Meters X Y Unique Number Verification Input Date																									
Angled Drill Hole																									
Well Contractor Northland Drilling, Inc. 1933 HINES, R Licensee Business Lic. or Reg. No. Name of Driller																									