

896441

County Becker

Quad

Quad ID

MINNESOTA DEPARTMENT OF HEALTH

WELL AND BORING REPORT

Minnesota Statutes Chapter 1031

Entry Date

Update Date04/30/2026

Received Date02/03/2026

Well Name BUTLER, JUDY	Township 142	Range 40	Dir Section W 26	Subsection ADA	Well Depth 80 ft.	Depth Completed 80 ft.	Date Well Completed 11/18/2025																																				
Elevation	Elev. Method					Drill Method Non-specified Rotary	Drill Fluid Bentonite																																				
Address C/W32756 355TH ST OGEMA MN 56569					Use domestic	Status Active																																					
					Well Hydrofractured? Yes☐No☒			From	To																																		
					Casing Type Single casing			Joint																																			
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>TOP SOIL</td><td>0</td><td>1</td><td>BLACK</td><td>SOFT</td></tr><tr><td>CLAY</td><td>1</td><td>3</td><td>GRAY</td><td>SOFT</td></tr><tr><td>SAND</td><td>3</td><td>32</td><td>GRAY</td><td>MEDIUM</td></tr><tr><td>CLAY</td><td>32</td><td>61</td><td>BROWN</td><td>SOFT</td></tr><tr><td>SANDY CLAY</td><td>61</td><td>68</td><td>GRAY</td><td>SOFT</td></tr><tr><td>SAND</td><td>68</td><td>80</td><td>GRAY</td><td>MEDIUM</td></tr></table>					Geological Material	From	To (ft.)	Color	Hardness	TOP SOIL	0	1	BLACK	SOFT	CLAY	1	3	GRAY	SOFT	SAND	3	32	GRAY	MEDIUM	CLAY	32	61	BROWN	SOFT	SANDY CLAY	61	68	GRAY	SOFT	SAND	68	80	GRAY	MEDIUM	Drive Shoe? Yes☐No☒	Above/Below		
					Geological Material	From	To (ft.)	Color	Hardness																																		
					TOP SOIL	0	1	BLACK	SOFT																																		
					CLAY	1	3	GRAY	SOFT																																		
					SAND	3	32	GRAY	MEDIUM																																		
					CLAY	32	61	BROWN	SOFT																																		
					SANDY CLAY	61	68	GRAY	SOFT																																		
					SAND	68	80	GRAY	MEDIUM																																		
					Casing Diameter 4 in. To 76 ft. 1 lbs./ft.		Hole Diameter 6.7 in. To 80 ft.																																				
					Open Hole <table><tr><td>From</td><td>ft.</td><td>To</td><td>ft.</td></tr></table>							From	ft.	To	ft.																												
From	ft.	To	ft.																																								
Screen? ☒	Type stainless		Make JOHNSON																																								
Diameter 4 in.	Slot/Gauze 10	Length 4 ft.	Set 76 ft.	To 80 ft.																																							
Static Water Level <table><tr><td>5 ft.</td><td>land surface</td><td>Measure</td><td>11/04/2025</td></tr></table>							5 ft.	land surface	Measure	11/04/2025																																	
5 ft.	land surface	Measure	11/04/2025																																								
Pumping Level (below land surface) <table><tr><td>75 ft.</td><td>1 hrs.</td><td>Pumping at</td><td>50 g.p.m.</td></tr></table>							75 ft.	1 hrs.	Pumping at	50 g.p.m.																																	
75 ft.	1 hrs.	Pumping at	50 g.p.m.																																								
Wellhead Completion <table><tr><td>Pitless adapter manufacturer</td><td>MONITOR</td><td>Model</td><td>SNAPPY</td></tr><tr><td>☐ Casing Protection</td><td colspan="3">☒ 12 in. above grade</td></tr><tr><td colspan="4">☐ At-grade (Environmental Wells and Borings ONLY)</td></tr></table>							Pitless adapter manufacturer	MONITOR	Model	SNAPPY	☐ Casing Protection	☒ 12 in. above grade			☐ At-grade (Environmental Wells and Borings ONLY)																												
Pitless adapter manufacturer	MONITOR	Model	SNAPPY																																								
☐ Casing Protection	☒ 12 in. above grade																																										
☐ At-grade (Environmental Wells and Borings ONLY)																																											
Grouting Information <table><tr><td colspan="2">Well Grouted?</td><td>☒ Yes</td><td>☐ No</td><td colspan="3">☐ Not Specified</td></tr><tr><td>Material</td><td>Amount</td><td>From</td><td>To</td><td colspan="3"></td></tr><tr><td>other</td><td>4 Sacks</td><td></td><td>ft. 50 ft.</td><td colspan="3"></td></tr></table>							Well Grouted?		☒ Yes	☐ No	☐ Not Specified			Material	Amount	From	To				other	4 Sacks		ft. 50 ft.																			
Well Grouted?		☒ Yes	☐ No	☐ Not Specified																																							
Material	Amount	From	To																																								
other	4 Sacks		ft. 50 ft.																																								
Nearest Known Source of Contamination <table><tr><td>80 feet</td><td>South Direction</td><td>Sewer Type</td></tr><tr><td colspan="2">Well disinfected upon completion?</td><td>☒ Yes☐ No</td></tr></table>							80 feet	South Direction	Sewer Type	Well disinfected upon completion?		☒ Yes ☐ No																															
80 feet	South Direction	Sewer Type																																									
Well disinfected upon completion?		☒ Yes ☐ No																																									
Pump <table><tr><td>☐ Not Installed</td><td>Date Installed</td><td colspan="5">11/18/2025</td></tr><tr><td colspan="7">Manufacturer's name PENTEK</td></tr><tr><td>Model Number</td><td>S10P4JP052</td><td>HP</td><td>0.5</td><td>Volt</td><td>230</td><td></td></tr><tr><td>Length of drop pipe</td><td>40 ft</td><td>Capacity</td><td>10 g.p.</td><td>Typ</td><td>Submersible</td><td></td></tr></table>							☐ Not Installed	Date Installed	11/18/2025					Manufacturer's name PENTEK							Model Number	S10P4JP052	HP	0.5	Volt	230		Length of drop pipe	40 ft	Capacity	10 g.p.	Typ	Submersible										
☐ Not Installed	Date Installed	11/18/2025																																									
Manufacturer's name PENTEK																																											
Model Number	S10P4JP052	HP	0.5	Volt	230																																						
Length of drop pipe	40 ft	Capacity	10 g.p.	Typ	Submersible																																						
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes☒ No																																											
Variance Was a variance granted from the MDH for this well? ☐ Yes☒ No																																											
Miscellaneous <table><tr><td>First Bedrock</td><td>Aquifer</td></tr><tr><td>Last Strat</td><td>Depth to Bedrock</td><td>ft</td></tr><tr><td colspan="3">Located by</td></tr><tr><td colspan="3">Locate Method</td></tr><tr><td>System</td><td>UTM - NAD83, Zone 15, Meters</td><td>X</td><td>Y</td></tr><tr><td colspan="2">Unique Number Verification</td><td colspan="2">Input Date</td></tr></table>							First Bedrock	Aquifer	Last Strat	Depth to Bedrock	ft	Located by			Locate Method			System	UTM - NAD83, Zone 15, Meters	X	Y	Unique Number Verification		Input Date																			
First Bedrock	Aquifer																																										
Last Strat	Depth to Bedrock	ft																																									
Located by																																											
Locate Method																																											
System	UTM - NAD83, Zone 15, Meters	X	Y																																								
Unique Number Verification		Input Date																																									
Angled Drill Hole																																											
Well Contractor <table><tr><td>Elsner Well Drilling, Inc.</td><td>1374</td><td>MONROE, W.</td></tr><tr><td>Licenses Business</td><td>Lic. or Reg. No.</td><td>Name of Driller</td></tr></table>							Elsner Well Drilling, Inc.	1374	MONROE, W.	Licenses Business	Lic. or Reg. No.	Name of Driller																															
Elsner Well Drilling, Inc.	1374	MONROE, W.																																									
Licenses Business	Lic. or Reg. No.	Name of Driller																																									