

896548

County Wright
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 05/04/2026
Update Date 05/04/2026
Received Date 01/23/2026

Well Name ZIEGLER	Township 122	Range 26	Dir W	Section 20	Subsection DAA	Well Depth 61 ft.	Depth Completed 61 ft.	Date Well Completed 11/05/2025
Elevation						Drill Method Non-specified Rotary	Drill Fluid Bentonite	
Address						Use domestic	Status Active	
Contact 11469 193RD AV NW ELK RIVER MN 55330						Well Hydrofractured? Yes ☐ No ☐ From To		
Well 14441 8 CR NW CLEARWATER MN						Casing Type Single casing Joint		
Stratigraphy Information						Drive Shoe? Yes ☐ No ☐ Above/Below		
Geological Material		From	To (ft.)	Color	Hardness	Casing Diameter Weight Hole Diameter		
SAND		0	18	BROWN	SOFT	4 in. To 53 ft. lbs./ft. 6.7 in. To 61 ft.		
CLAY/GRAVEL/ ROCKY		18	50	GRAY	MEDIUM			
SAND		50	61	DARK	SOFT			
Open Hole						From ft. To ft.		
Screen? ☒						Type stainless Make JOHNSON		
Diameter		Slot/Gauze		Length		Set		
3 in.		15		8 ft.		53 ft.		61 ft.
Static Water Level						17 ft. land surface Measure 11/05/2025		
Pumping Level (below land surface)						60 ft. 1.5 hrs. Pumping at 35 g.p.m.		
Wellhead Completion						Pitless adapter manufacturer BAKER Model BULLDOG		
☐ Casing Protection						☒ 12 in. above grade		
☐ At-grade (Environmental Wells and Borings ONLY)								
Grouting Information						Well Grouted? ☒ Yes ☐ No ☐ Not Specified		
Material		Amount		From To				
bentonite		5 Sacks		ft. 50 ft.				
Nearest Known Source of Contamination						80 feet <u>Northeas</u> Direction <u>Sewer</u> Type		
Well disinfected upon completion?						☒ Yes ☐ No		
Pump ☐ Not Installed						Date Installed <u>01/10/2026</u>		
Manufacturer's name STA-RITE								
Model Number		<u>VFD</u>	HP	<u>1</u>	Volt	<u>230</u>		
Length of drop pipe		<u>40</u>	ft	Capacity	<u>20</u>	g.p.	Typ	<u>Submersible</u>
Abandoned						Does property have any not in use and not sealed well(s)? ☐ Yes ☐ No		
Variance						Was a variance granted from the MDH for this well? ☐ Yes ☒ No		
Miscellaneous						First Bedrock Aquifer		
Last Strat						Depth to Bedrock ft		
Located by								
Locate Method								
System		UTM - NAD83, Zone 15, Meters				X	Y	
Unique Number Verification						Input Date		
Angled Drill Hole								
Well Contractor						Driven Drilling, LLC 3346 MOTZKO, J		
Licensee Business						Lic. or Reg. No.		Name of Driller