

896926

County Itasca
Quad Wirt
Quad ID 325B

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date

Update Date01/13/2026

Received Date12/16/2025

Well Name PARENTEAU, Township 149 Range 26 Dir Section W 22 Subsection CACCCA	Well Depth 101 ft. Depth Completed 101 ft. Date Well Completed 11/24/2025																				
Elevation 1352 Elev. Method LiDAR 1m DEM (MNDNR)	Drill Method Non-specified Rotary Drill Fluid Bentonite																				
Address Well57274 JOHNSON RD WIRT 56688 Contact4696 SANDRA LA WHITE BEAR LAKE MN 55110	Use domestic Status Active																				
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>CLAY</td><td>0</td><td>18</td><td>BROWN</td><td>MEDIUM</td></tr><tr><td>CLAY</td><td>18</td><td>92</td><td>GRAY</td><td>MEDIUM</td></tr><tr><td>SAND</td><td>92</td><td>101</td><td>GRAY</td><td>SOFT</td></tr></table>	Geological Material	From	To (ft.)	Color	Hardness	CLAY	0	18	BROWN	MEDIUM	CLAY	18	92	GRAY	MEDIUM	SAND	92	101	GRAY	SOFT	Well Hydrofractured? Yes☐ No☒ From To
	Geological Material	From	To (ft.)	Color	Hardness																
	CLAY	0	18	BROWN	MEDIUM																
	CLAY	18	92	GRAY	MEDIUM																
	SAND	92	101	GRAY	SOFT																
	Casing Type Single casing Joint	Drive Shoe? Yes☐ No☒ Above/Below																			
	Casing Diameter 4 in. To 93 ft. Weight lbs./ft. Hole Diameter 8 in. To 101 ft.																				
	Open Hole From ft. To ft.																				
	Screen? ☒ Type stainless Make JOHNSON																				
	Diameter 2 in. Slot/Gauze 10 Length 8 ft. Set 93 ft. 101 ft.																				
Static Water Level 18 ft. land surface Measure 11/24/2025																					
Pumping Level (below land surface) 50 ft. 2 hrs. Pumping at 40 g.p.m.																					
Wellhead Completion Pitless adapter manufacturer MONITOR Model SNAPPY																					
☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																					
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified																					
Material bentonite Amount 4 Sacks From To ft. 50 ft.																					
Nearest Known Source of Contamination 60 feet Northwes Direction Sewer Type																					
Well disinfected upon completion? ☒ Yes ☐ No																					
Pump ☐ Not Installed Date Installed 11/24/2025																					
Manufacturer's name GRUNDFOS																					
Model Number 10SQ07-200 HP 0.75 Volt 230																					
Length of drop pipe 50 ft Capacity 10 g.p. Typ Submersible																					
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																					
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																					
Remarks	Miscellaneous First Bedrock Aquifer Quat. buried																				
	Last Strat sand-gray Depth to Bedrock ft																				
	Located by Minnesota Geological Survey																				
	Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or																				
	System UTM - NAD83, Zone 15, Meters X 427811 Y 5284007																				
	Unique Number Verification Address verification Input Date 01/13/2026																				
	Angled Drill Hole																				
	Well Contractor Antlers Well Drilling 1448 PINK, T																				
	Licensee Business Lic. or Reg. No. Name of Driller																				

Minnesota Well Index Report

896926

Printed on 08/13/2026
HE-01205-15