

897094

County Benton
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 03/02/2026
Update Date 03/02/2026
Received Date 01/27/2026

Well Name IMHOLTE	Township 36	Range 29	Dir W	Section 36	Subsection DCB																														
Elevation Elev. Method																																			
Address Well 135TH AV SE FOLEY MN 56329 Contact 7934 62ND AV CLEAR LAKE MN 55319																																			
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>TOP SOIL</td><td>0</td><td>3</td><td>BLACK</td><td>SOFT</td></tr><tr><td>SAND</td><td>3</td><td>13</td><td>BROWN</td><td>SOFT</td></tr><tr><td>CLAY</td><td>13</td><td>24</td><td>BROWN</td><td>MEDIUM</td></tr><tr><td>SAND/ GRAVEL</td><td>24</td><td>47</td><td>BROWN</td><td>SOFT</td></tr><tr><td>CLAY</td><td>47</td><td>47</td><td>GRAY</td><td>MEDIUM</td></tr></table>						Geological Material	From	To (ft.)	Color	Hardness	TOP SOIL	0	3	BLACK	SOFT	SAND	3	13	BROWN	SOFT	CLAY	13	24	BROWN	MEDIUM	SAND/ GRAVEL	24	47	BROWN	SOFT	CLAY	47	47	GRAY	MEDIUM
Geological Material	From	To (ft.)	Color	Hardness																															
TOP SOIL	0	3	BLACK	SOFT																															
SAND	3	13	BROWN	SOFT																															
CLAY	13	24	BROWN	MEDIUM																															
SAND/ GRAVEL	24	47	BROWN	SOFT																															
CLAY	47	47	GRAY	MEDIUM																															
Well Depth 47 ft. Depth Completed 47 ft. Date Well Completed 12/31/2025																																			
Drill Method Non-specified Rotary Drill Fluid Qwik gel																																			
Use irrigation Status Active																																			
Well Hydrofractured? Yes ☐ No ☒ From To																																			
Casing Type Single casing Joint																																			
Drive Shoe? Yes ☐ No ☒ Above/Below																																			
Casing Diameter 8 in. Weight 28.55 lbs./ft. Hole Diameter 12 in.																																			
Open Hole From ft. To ft.																																			
Screen? ☒ Type stainless Make JOHNSON																																			
Diameter 8 in. Slot/Gauze 100 Length 10 ft. Set 37 ft. ft. 47 ft.																																			
Static Water Level 1 ft. land surface Measure 12/31/2025																																			
Pumping Level (below land surface) ft. hrs. Pumping at g.p.m.																																			
Wellhead Completion Pitless adapter manufacturer Model ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																																			
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified																																			
Material bentonite Amount 6 Sacks From 1 ft. To 27 ft.																																			
Nearest Known Source of Contamination 60 feet South Direction Body of water Type																																			
Well disinfected upon completion? ☒ Yes ☐ No																																			
Pump ☒ Not Installed Date Installed																																			
Manufacturer's name																																			
Model Number HP Volt																																			
Length of drop pipe ft Capacity g.p. Typ																																			
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																																			
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																																			
Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft Located by Locate Method System UTM - NAD83, Zone 15, Meters X Y Unique Number Verification Input Date																																			
Angled Drill Hole																																			
Well Contractor Mark J Traut Wells, Inc. 1404 REMARKS Licensee Business Lic. or Reg. No. Name of Driller																																			