

897343

County Lake of The
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date04/10/2026

Update Date04/10/2026

Received Date12/11/2025

Well Name UBEL, LODIA	Township 162	Range 33	Dir W	Section 32	Subsection AAA																																								
Elevation	Elev. Method																																												
Address Contact1202 1 CR SW BAUDETTE MN 56623 Well2775 66TH AV NW WILLIAMS MN 56686																																													
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>CLAY</td><td>0</td><td>6</td><td>BROWN</td><td>MEDIUM</td></tr><tr><td>CLAY</td><td>6</td><td>30</td><td>GRAY</td><td>MEDIUM</td></tr><tr><td>FINE SAND</td><td>30</td><td>31</td><td>GRAY</td><td>SOFT</td></tr><tr><td>CLAY</td><td>31</td><td>86</td><td>GRAY</td><td>SOFT</td></tr><tr><td>SAND</td><td>86</td><td>90</td><td>GRAY</td><td>MEDIUM</td></tr><tr><td>ROCK & COARSE</td><td>90</td><td>96</td><td>GRAY</td><td>HARD</td></tr><tr><td>CLAY</td><td>96</td><td>100</td><td>WHITE</td><td>MEDIUM</td></tr></table>						Geological Material	From	To (ft.)	Color	Hardness	CLAY	0	6	BROWN	MEDIUM	CLAY	6	30	GRAY	MEDIUM	FINE SAND	30	31	GRAY	SOFT	CLAY	31	86	GRAY	SOFT	SAND	86	90	GRAY	MEDIUM	ROCK & COARSE	90	96	GRAY	HARD	CLAY	96	100	WHITE	MEDIUM
Geological Material	From	To (ft.)	Color	Hardness																																									
CLAY	0	6	BROWN	MEDIUM																																									
CLAY	6	30	GRAY	MEDIUM																																									
FINE SAND	30	31	GRAY	SOFT																																									
CLAY	31	86	GRAY	SOFT																																									
SAND	86	90	GRAY	MEDIUM																																									
ROCK & COARSE	90	96	GRAY	HARD																																									
CLAY	96	100	WHITE	MEDIUM																																									
Well Depth 100 ft.																																													
Depth Completed 95 ft.																																													
Date Well Completed 11/03/2025																																													
Drill Method Non-specified Rotary																																													
Drill Fluid Bentonite																																													
Use domestic																																													
Status Active																																													
Well Hydrofractured? Yes☐ No☒ From To																																													
Casing Type Single casing																																													
Joint Glued																																													
Drive Shoe? Yes☐ No☒ Above/Below																																													
Casing Diameter Weight Hole Diameter																																													
4 in. To 87 ft. 1.9 lbs./ft. 8 in. To 20 ft. 6.7 in. To 100 ft.																																													
Open Hole From ft. To ft.																																													
Screen? ☒																																													
Type stainless																																													
Make JOHNSON																																													
Diameter Slot/Gauze Length Set																																													
4 in. 7 8 ft. 87 ft. 95 ft.																																													
Static Water Level 4 ft. land surface Measure 11/03/2025																																													
Pumping Level (below land surface) ft. hrs. Pumping at 3 g.p.m.																																													
Wellhead Completion Pitless adapter manufacturer MONITOR Model BULLDOG																																													
☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																																													
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified																																													
Material Amount From To																																													
bentonite 4 Sacks ft. 75 ft.																																													
Nearest Known Source of Contamination 125 feet South Direction Sewer Type																																													
Well disinfected upon completion? ☒ Yes ☐ No																																													
Pump ☐ Not Installed Date Installed 10/20/2025																																													
Manufacturer's name GRUNDFOS																																													
Model Number 10SQ07200																																													
HP 0.75																																													
Volt 230																																													
Length of drop pipe 78 ft																																													
Capacity 10 g.p.																																													
Typ Submersible																																													
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																																													
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																																													
Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft																																													
Located by Locate Method System UTM - NAD83, Zone 15, Meters																																													
X Y Unique Number Verification Input Date																																													
Angled Drill Hole																																													
Well Contractor Calder Well Drilling, Inc. 1663 CALDER, B Licensee Business Lic. or Reg. No. Name of Driller																																													
Remarks																																													
Minnesota Well Index Report 897343 Printed on 08/13/2026 HE-01205-15																																													