

985515

County Otter Tail
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 04/29/2026
Received Date 02/03/2026

Well Name LIEN, LYNETTE					Township 136	Range 42	Dir W	Section 2	Subsection BBD	Well Depth 38 ft.		Depth Completed 38 ft.		Date Well Completed 11/17/2025													
Elevation					Elev. Method					Drill Method Non-specified Rotary		Drill Fluid Bentonite															
Address C/W 26140 CRYSTAL PT DR PELICAN RAPIDS MN										Use domestic		Status Active															
Stratigraphy Information Geological Material From To (ft.) Color Hardness TOP SOIL 0 1 BLACK SOFT CLAY 1 27 YELLOW SOFT 27 31 BLUE SOFT SAND 31 38 GRAY SOFT										Well Hydrofractured?		Yes ☐		No ☒		From		To									
										Casing Type		Single casing		Joint													
										Drive Shoe?		Yes ☐		No ☒		Above/Below											
										Casing Diameter		Weight		Hole Diameter													
										4 in. To		31 ft. 1 lbs./ft.		6.7 in. To 38 ft.													
										Open Hole										From		ft.		To		ft.	
										Screen?		☒		Type		stainless		Make		JOHNSON							
										Diameter		Slot/Gauze		Length		Set		ft.		31 ft.		38 ft.					
										4 in.		12		7 ft.		ft.		ft.		ft.		ft.					
										Static Water Level										13 ft.		land surface		Measure		11/17/2025	
Pumping Level (below land surface)										30 ft.		1 hrs.		Pumping at		30 g.p.m.											
Wellhead Completion										Pitless adapter manufacturer		MONITOR		Model		PITLESS											
☐ Casing Protection										☒ 12 in. above grade																	
☐ At-grade (Environmental Wells and Borings ONLY)																											
Grouting Information										Well Grouted?		☒ Yes		☐ No		☐ Not Specified											
Material										Amount		From		To													
other										3 Sacks		ft.		30 ft.		ft.											
Nearest Known Source of Contamination										feet		Direction				Type											
Well disinfected upon completion?										☒ Yes		☐ No															
Pump										☐ Not Installed		Date Installed		11/17/2025													
Manufacturer's name										STA-RITE																	
Model Number										S2OP4JP205		HP		1		Volt		230									
Length of drop pipe										20 ft		Capacity		20 g.p.		Typ		Submersible									
Abandoned										Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																	
Variance										Was a variance granted from the MDH for this well? ☐ Yes ☒ No																	
Miscellaneous										First Bedrock										Aquifer							
Last Strat																				Depth to Bedrock		ft					
Located by																											
Locate Method																											
System										UTM - NAD83, Zone 15, Meters		X		Y													
Unique Number Verification																				Input Date							
Angled Drill Hole																											
Well Contractor										Elsner Well Drilling, Inc.										1374		MONROE, S					
Licensee Business										Lic. or Reg. No.										Name of Driller							